

Model	RG-ES105GD	RG-ES108GD	RG-ES109G-LP-L	RG-ES126G-P-L	RG-ES126G-LP-L
Hardware specifications					
Ports	5*10/100/1000Mbps RJ45 ports	8*10/100/1000 Mbps RJ45 ports	8*10/100/1000 Mbps PoE/PoE+ Ports	24*10/100/1000 Mbps PoE/PoE+ Ports	24*10/100/1000 Mbps PoE/PoE+ Ports
	N/A	N/A	1*10/100/1000 Mbps uplink port	2*1000Mbps SFP port	2*1000Mbps SFP port
Operating mode	Half-duplex, full-duplex, auto-negotiation mode Support auto MDI/MDIX				
Switching capacity	10Gbps	16Gbps	18Gbps	52Gbps	52Gbps
Package forwarding rate	7.44Mpps	11.9Mpps	13.5Mpps	39Mpps	39Mpps
Power supply	External 5VDC 1.0A		100-240V AC		
Surge protection	Not Support		Adapter:	Switch-mode power supply:	
			Common mode: ±4 kV	Common mode: ±6 kV	
			Differential mode: ±2 kV	Differential mode: ±6 kV	
			Network ports:	Network ports:	
			Non-PoE ports: ±4 kV	Non-PoE ports: ±4 kV	
			PoE ports: ±6 kV		
Port Mode	Not Support		Flow Control On/Off Port Isolation		
Power consumption	≤5W		64W	430W	220W
PoE power budget	N/A		54W	370W	180W
Fan	N/A		NA	Support	Support
Dimensions (W x D x H)	119 x 62 x 24mm	160 x 75 x 24mm	206.5 x 108.5 x 28mm	440 x 205 x 43.6mm	440 x 205 x 43.6mm
Operating temperature	0°C to 40°C		0°C to 45°C		
Storage temperature	-40°C to 70°C		-40°C to 70°C		
Operating humidity	10% to 90% RH		5% to 90% RH		
Storage humidity	5% to 95% RH		5% to 95% RH		

לונסטאר תקשורת לעסקים
טלפון : 0722-770-670
מייל מכירות : Sales@lonestar-sys.co.il
מייל תמיכה : Support@lonestar-sys.co.il